

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WDE-50 DEHUMIDIFIER

Specification

- 3 in 1 - dehumidifier, air - purifier and dryer
- Moisture removal: 50 liters / day
- Water tank capacity: 6.5 liters
- 24 hours timer
- Power controls: LCD Display / Touch Control
- Automatic humidity control
- Auto frost control
- Air - purifying filter
- Full water tank warning signal
- Continuous drainage
- Power rotary compressor
- Easier mobility with convenient Wheels
- Recyclable materials for environmental conservation
- R - 410A refrigerant
- Running temperature: 5° C - 35° C
- Voltage / frequency (Volts/Hz): 220 - 240 V, 50Hz
- Power input (Watt): 900 W

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....

Technical Specification

Refrigerant	: R410
cover area	: 5000 cu.ft. -5500 cu.ft
Air Flow	: 306m ³ /h
Sound DB Level	: 52.39
Moisture Removal Cap	: 50 ltr per day (temp 30 degree C, RH80%)
RH setting	: (30% to 80%)
compressor	: rotary
Working Range	: 5 degree C to 35 degree C
control automatic, Digital Control	: Yes
Power input	: 900w
Current	: 4.3A
Power supply	: 220-240, 50 Hz

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WD-551

- 3 in 1 –Dehumidifier, Air-Purifier and Dryer
- Energy Efficiency Grade 2
- Moisture Removal (Running Temperature): 30 L/Day (26.7°C 60%RH) / 55 L /Day (30°C 80%RH)
- Water Tank Capacity 5 L
- Power Controls: Mechanical Control
- Humidity Sensor
- Auto Defrost
- Full Water Tank Warning Signal
- Easy Wheels
- Energy saving rotary compressor
- Extremely Silent
- Air-Purifying Filter
- Continuous Drainage
- Easier Mobility with Convenient Wheels
- Recyclable materials for Environmental Conservation

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WDE-371

- 3 in 1 –Dehumidifier, Air-Purifier and Dryer
- Energy Efficiency Grade 3
- Moisture Removal: 24.5 L/Day (26.7°C 60%RH) / 37 L /Day (30°C 80%RH)
- Power input (Watt) : 575W (26.7°C 60%RH) / 640W (30°C 80%RH)
- Running Temperature: 5°C - 32°C
- Water Tank Capacity : 4L
- Timer (1-12 hours)
- Power Controls: Electronic Control
- Humidity Sensor
- Auto Defrost
- Full Water Tank Warning Signal
- Easy Wheels
- Energy saving rotary compressor
- Extremely Silent
- Air-Purifying Filter
- Continuous Drainage
- Easier Mobility with Convenient Wheels
- Recyclable materials for Environmental Conservation
- Dimensions (HxWxD): 594x380x305mm, 23.4x15x12 inch
- Db level: 51.34
- Air Flow: 306m³/h

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WDE-301

Features

- 3 in 1 – Dehumidifier, Air-Purifier and Dryer
- Dehumidifying Capacity: 30 Liters per day
- Water Tank Capacity: 4 Liters
- Power Controls: Micro Controller
- 2 Fan Speed
- Automatic humidistat Control
- Auto Frost Control
- Air-Purifying Filter
- Automatic Reset
- Full Water Tank Warning Signal
- Continuous Drainage
- Top air outlet for drying clothes
- Extremely Silent
- Easier Mobility with Convenient Wheels
- Power Rotary Compressor
- Recyclable materials for Environmental Conservation
- R-410a Refrigerant
- Running Temperature: 5°C ~ 32°C
- Power Input (Watt): 600W
- Dimensions (H x W x D): 610x 390 x 274 mm

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....

Technical Specification

- Refrigerant : R410a
- Cover Area : 3000 Cu.Ft - 3500 Cu.Ft
- Air Flow : 204 M³ / H
- Sound DB Level : 47.43
- Moisture Removal Cap : 30 Ltr Per Day (Temp 30 Degree C, RH80%)
- RH Setting : (30% To 80%)
- Compressor : Rotary
- Working Range : 5 Degree C To 32 Degree C
- Control Automatic, Digital Control : Yes
- Power Input : 600w
- Current : 2.5A
- Power Supply : 220-240, 50 Hz

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WDE-221

- 3 in 1 –Dehumidifier, Air-Purifier and Dryer
- Energy Efficiency Grade 1
- Moisture Removal (Running Temperature): 13 L (26.7°C 60%RH)/ 22 L (30°C 80%RH)
- Water Tank Capacity 4.5L
- Power Controls: LCD Display / Touch Control
- Humidity Sensor
- Auto Defrost
- Full Water Tank Warning Signal
- Easy Wheels
- Energy saving rotary compressor
- Extremely Silent
- Air-Purifying Filter
- Continuous Drainage
- Easier Mobility with Convenient Wheels
- Recyclable materials for Environmental Conservation
- Dimensions (HxWxD): 530x320x245mm, 20.9x12.6x9.6inch

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WDE-181

- 3 in 1 –Dehumidifier, Air-Purifier and Dryer
- Energy Efficiency Grade 1
- Moisture Removal: 9.5 L/Day (26.7°C 60%RH) / 18 L /Day (30°C 80%RH)
- Power input (Watt) : 225W (26.7°C 60%RH) / 240W (30°C 80%RH)
- Running Temperature: 5°C - 32°C
- Water Tank Capacity : 4.5L
- Timer (1-12 hours)
- Power Controls: LCD Display / Electronic Control
- Humidity Sensor
- Auto Defrost
- Full Water Tank Warning Signal
- Easy Wheels
- Energy saving rotary compressor
- Extremely Silent
- Air-Purifying Filter
- Continuous Drainage
- Easier Mobility with Convenient Wheels
- Recyclable materials for Environmental Conservation
- Dimensions (HxWxD): 530x320x245mm, 20.9x12.6x9.6 inch

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WDE-121

- Rated voltage/Frequency (V~Hz) 220-240V/50Hz
- Moisture removal 6L/D (27°C/60%RH) / 12L/D (30°C/80%RH)
- Rated input 195W
- Refrigerant gas R-134a
- Timer 24h count-down
- Fan speed 4
- Full water capacity(l) /Tank capacity (l) 2.1L
- Visible water level Yes
- Adjustable humidistat Yes
- Hygrometer/Thermometer Yes
- Anti dust filter Yes
- Continuous drainage Yes
- Electronic anti-defrost device Yes
- Working temperature 5°C-32°C
- Unit dimension (W*D*H) in 303*193*468 MM

World Class DEHUMIDIFIERS from
White WestingHouse
USA

Products That Deliver The Ultimate In Performance.....



WDE-205

- Rated voltage/Frequency (V~Hz) 220-240V/50Hz
- Moisture removal 12L/D (27°C/60%RH) 20L/D (30°C/80%RH)
- Rated input 380W
- Refrigerant gas R-410a
- Timer 24h count-down
- Fan speed 2
- Full water capacity(l) /Tank capacity (l) 4.2L
- Visible water level No
- Adjustable humidistat Yes
- Hygrometer/Thermometer Yes
- Anti dust filter Yes
- Continuous drainage Yes
- Electronic anti-defrost device Yes
- Working temperature 5°C-32°C
- Unit dimension (W*D*H) in mm 390*274*612